



BRAINY



100%
Made in Italy



APPLICATION

1 or 2 actuators for swing gates, opposed sliding gates, hydraulic operators, and industrial folding doors

CONTROL UNIT POWER SUPPLY

230 Vac

MOTORS POWER SUPPLY

230 Vac 600W + 600W

MAIN FUNCTIONS

Integrated LCD display | Integrated 433.92 MHz 64-code radio receiver with 3 encoding systems (Advanced Rolling Code, Rolling Code, Fixed Code) | Removable terminal boards | Automatic, semi-automatic and deadman's logic | Encoder input to detect obstacles | Separate limit switch inputs for each motor | Open, close, pedestrian, step by step and stop inputs | Separate photocell inputs in opening-closing and in closing phases | Input for N.C or 8K2 sensitive edge | Output for electric lock 230 VAC and 12 VAC/DC | Outputs for configuration as gate open indicator, service light, second radio channel and photocell testing | Autosetting of operating parameters (with motors equipped with encoder) | Separate electronic torque adjustment for each motor and operating times | Adjustable slow-downs | Advantouch system to configure parameters and manage radio transmitters | Number of maneuvers | Programming access password | Maintenance warning



DU.V96

12 Vac/dc vertical electric lock, supplied with counterplate. Permits internal/external release.



DU.V90

12 Vac/dc horizontal electric lock, supplied with counterplate. Permits internal/external release.



DU.9990

Covering plate for DU.V90.



E.LOCK

230 Vac vertical electric lock, supplied with counterplate.



E.LOCKSE

Extended cylinder for E.LOCK electric lock. It allows unlocking gates up to 55mm-thick from the outside.



BRAINY.P

BRAINY control units with open, close, stop buttons incorporated in the control unit.

AUTOMATISMI BENINCA SpA • Via del Capitello, 45 • 36066 Sandrigo (VI) ITALY • T +39 0444 751030 • sales@beninca.com

