



BRAINY24



100%
Made in Italy



APPLICATION

1 or 2 actuators for swing gates, opposed sliding gates, and industrial folding doors with a maximum of 2 sections

CONTROL UNIT POWER SUPPLY

230 Vac – 50/60 Hz

MOTORS POWER SUPPLY

24 Vdc 120W + 120W

MAIN FUNCTIONS

Integrated LCD display | Integrated 433.92 MHz 64-code receiver with 3 encoding systems (Advanced Rolling Code, Rolling Code, Fixed Code) | Removable terminal boards | Separate limit switch inputs for each motor | Open, close, and pedestrian inputs | Photocell inputs in opening-closing and in closing phases | Input for N.C. or 8K2 sensitive edge | Output for electric lock 12 VDC | Output for configuration as gate open indicator, service light, second radio channel and photocell testing | Autosetting of operating parameters | Separate electronic torque adjustment for each motor | Anti-crushing safety through amperometric detection and encoder management | Separate adjustable slowdowns for each motor in opening and closing phases | Advantouch system to configure parameters and manage radio transmitters | Number of maneuvers | Programming access password | Maintenance warning



DU.V96

12 Vac/dc vertical electric lock, supplied with counterplate. Permits internal/external release.




DU.V90

12 Vac/dc horizontal electric lock, supplied with counterplate. Permits internal/external release.



DU.9990

Covering plate for DU.V90.



BRAINY24.CB

Accessory with CBY.24V battery charger, 1.2 Ah batteries and support bracket.



BRAINY24.P

BRAINY24 control units with open, close, stop buttons incorporated in the control unit.

AUTOMATISMI BENINCA SpA • Via del Capitello, 45 • 36066 Sandrigo (VI) ITALY • T +39 0444 751030 • sales@beninca.com

